## FULL VERSION OF PENDING CLAIMS

- 1 Claim 1 (Original): A lighting apparatus for a liquid crystal display comprising:
- a. an array of light emitting diodes disposed alongside said liquid crystal display
   for providing illumination thereof;
- b. light pipes for transmitting light from said light emitting diodes across a plane parallel with said liquid crystal display; and,
- 6 c. a filter disposed between said array and said light pipes for filtering out infra-7 red light from said light emitting diodes.
- Claim 2 (Original): An apparatus as in Claim 1 wherein said array of light emitting diodes include diodes emitting only red light.
- 1 Claim 3 (Original): An apparatus as in Claim 1 wherein said array of light emitting 2 diodes include diodes emitting only blue light.
- Claim 4' (Original): An apparatus as in Claim 1 wherein said array of light emitting diodes include diodes emitting only green light.
- Claim 5 (Currently Amended): An apparatus as in Claim 1 including a pair of light
  emitting diode arrays disposed on two sides of said light pipes with a filter disposed between
  each light emitting diode array and the light pipes, each filter for filtering out infra-red light
  from each light emitting diode array.
- Claim 6 (Original): An apparatus as in Claim 5 including a pair of infra-red filters disposed between each of said arrays of light emitting diodes and said light pipes.
- 1 Claim 7 (Original): An improved lighting apparatus for a liquid crystal display in the cockpit of an aircraft, said apparatus comprising:
  - a. a pair of light emitting diode arrays disposed alongside said liquid crystal display for providing illumination thereof;
- b. light pipes for transmitting light from said light emitting diode arrays across a
   plane parallel with and alongside said liquid crystal display; and,
  - c. filters disposed between each of said arrays and said light pipes for filtering out infra-red light from said light emitting diodes.



3

4

7

8

2

light.

. 1	Claim 8	(Original): An apparatus as in Claim 7 wherein each of said arrays of light			
2	emitting diodes include diodes emitting only red light.				
1	Claim 9	(Original): An apparatus as in Claim 7 whencin such of said amous of light			
		(Original): An apparatus as in Claim 7 wherein each of said arrays of light			
2	emitting diod	es include diodes emitting only blue light.			
1	Claim 10	(Original): An apparatus as in Claim 7 wherein each of said arrays of light			
2	emitting diod	es include diodes emitting only green light.			
1	Claim 11	(Original): A method for illuminating a liquid crystal display for viewing by:			
2	a.	activating an array of light emitting diodes of a first color adjacent light pipes			
3	disposed alongside said liquid crystal display; and,				
4	b.	filtering infra-red light emitted by said array of light emitting diodes.			
7	0.	intering inita-red light entitled by said array of light entitling diodes.			
1	Claim 12	(Original): The method as in Claim 11 wherein said first color is red.			
1	Claim 13	(Original): The method as in Claim 11 wherein said first color is green.			
1	Claim 14	(Original): The method as in Claim 11 wherein said first color is blue.			
1	Claim 15	(Original): A method for illuminating a liquid crystal display in an aircraft			
2	cockpit for viewing by a pilot wearing infra-red goggles, said method comprising:				
3	a.	activating an array of light emitting diodes adjacent light pipes disposed			
4	alongside said liquid crystal display;				
5	b.	filtering infra-red light emitted by said array of light emitting diodes; and,			
6	c.	switching colors of said light emitting diodes as required by a pilot of the			
7	aircraft.	,			
1	Claim 16	(Currently Amended): The method as in Claim 115 wherein said step of			
2	Claim 16 (Currently Amended): The method as in Claim 115 wherein said step of				
	switching colors further includes switching on only those light emitting diodes emitting red				
3	light.				
1	Claim 17	(Currently Amended): The method as in Claim 1+5 wherein said step of			

switching colors further includes switching on only those light emitting diodes emitting blue

3

34261-6300 Amendment.doc

1	Claim 18 (Currently Amended): The method as in Claim 115 wherein said step of				
2	switching colors further includes switching on only those light emitting diodes emitting green				
3					
1	Claim 19 (New): A multi-color lighting apparatus for a liquid crystal display,				
2	comprising:				
3	a. an array of light emitting diodes disposed alongside a plane perpendicular to				
4	the liquid crystal display for providing illumination thereof,				
5	the array comprising a plurality of different color light emitting diodes				
6	for emitting light of more than one color,				
7	the light emitting diodes of each color being addressable together as a				
8	color group,				
9	each color group corresponding to a wavelength of light that is adapted				
10	to illuminate a LCD display for viewing with a predetermined type of night-vision				
11	equipment;				
12	b. light pipes for transmitting light from the light emitting diodes across a plane				
13	parallel with the liquid crystal display, the transmitted light illuminating the liquid crystal				
14	display;				
15	c. an infra-red filter disposed between the array and the light pipes for filtering				
16	out infra-red light from the light emitting diodes of all color groups in the array; and				
17	d. a switch for selectively powering each color group of light emitting diodes in				
18	the array, each switch being used together or separately so that each of the color groups may				
19	be selectively powered.				
1	Claim 20 (New): A method of multi-color illumination for a liquid crystal display,				
2	comprising the steps of:				
3	a. selectively activating one or more color groups from an array of light emitting				
4	diodes,				
5	the array comprising a plurality of different color light emitting diodes				
6	for emitting light of more than one color,				
7	the light emitting diodes of each color being individually addressable				
8	together as a color group,				

9

10

to illuminate a LCD display for viewing with a predetermined type of night-vision

each color group corresponding to a wavelength of light that is adapted

•	•	
I	I	equipment;

- b. filtering infra-red light from the light emitting diodes of all color groups; and
- c. transmitting filtered light from the activated light emitting diodes into light
- 14 pipes for transmitting light across a plane parallel with the liquid crystal display, the
- 15 transmitted light illuminating the liquid crystal display.